

Application

Luminaires with direct and indirect light, to illuminate both the mounting surface and the desired space. Luminaires in this series are also available with an identical cover made of impact-resistant synthetic material for special applications, add P suffix to luminaire catalog number.

Materials

Hand-blown three-ply opal glass
Aluminum housing
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 13.2lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	37.8 W
System wattage	43.5 W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 80
Luminaire lumens	3522lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

White (.1)	Silver (.2)
------------	-------------



Type:
BEGA Product:
Project:
Modified:



Ceiling and wall luminaire · Opal glass · Direct/Indirect					
		LED	A	B	C
B12165	ADA	37.8 W	19 ³ / ₄	3 ³ / ₄	14 ¹ / ₄