

Application

Recessed wall luminaire with unshielded light that has a directing and guiding light effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

Materials

- Clear safety glass with white ceramic coating
- Die-cast aluminum
- Stainless steel screw clamps
- Mechanically captive stainless steel fasteners
- High temperature silicone gasket
- Aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 0.5 lbs.

Electrical

LED module wattage	2.1 W
System wattage	3.0 W
Color rendering index	Ra > 80
Luminaire lumens	21 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish


Available accessories

B19591	Remote driver box · Static white
--------	----------------------------------

See individual accessory spec sheet for details.

Included (available for pre-shipment)

BB2100LED	Installation housing
-----------	----------------------



Recessed wall luminaire · Unshielded · 24V DC				
		LED	A	B
B22109	ADA	2.1 W	3 1/8	4