

Application

Designed for low mounting heights for interior and exterior locations, the unshielded luminaire has a directing and guiding lighting effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

Materials

- Clear safety glass with white ceramic coating
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 64

Weight: 4.5 lbs.

Electrical

|                           |                                |
|---------------------------|--------------------------------|
| Operating voltage         | 120-277VAC                     |
| Minimum start temperature | -30° C                         |
| LED module wattage        | 6.7 W                          |
| System wattage            | 8.2W                           |
| Controllability           | 0-10V, TRIAC, and ELV dimmable |
| Color rendering index     | Ra > 80                        |
| Luminaire lumens          | 93 lm                          |
| LED service life (L70)    | 60000 hrs                      |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:


Available accessories

- B19536 Concrete protection cover

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- BB2034LED Installation housing



| Recessed wall luminaire · Unshielded |     |       |                                |                               |   |
|--------------------------------------|-----|-------|--------------------------------|-------------------------------|---|
|                                      |     | LED   | A                              | B                             | C |
| B22131                               | ADA | 6.7 W | 10 <sup>3</sup> / <sub>8</sub> | 3 <sup>1</sup> / <sub>8</sub> | 4 |

