

Application

Designed for low mounting heights for interior and exterior locations, the unshielded luminaire has a directing and guiding lighting effect. The illuminance level on the lit surface is lower, but the ambient brightness is greater with increased vertical illuminance.

Materials

- Clear safety glass with white ceramic coating
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 5.5 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	10.1 W
System wattage	11.5 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	91 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:
BEGA Product:
Project:
Modified:


Available accessories

- B19601 Concrete protection cover

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- BB2035LED Installation housing



Recessed wall luminaire · Unshielded					
		LED	A	B	C
B22132	ADA	10.1 W	12 ³ / ₄	3 ¹ / ₈	4

