

Application

Designed for low mounting heights for interior and exterior locations, the shielded light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs, and footpaths.

Materials

Clear safety glass with optical texture
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Corrosion-resistant 304 grade stainless steel
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 4.5 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	3.4 W
System wattage	4.9 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	9 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:

Available options

AMB	Amber LED
FSC	Fusing


Available accessories

B19535	Concrete protection cover
--------	---------------------------

See individual accessory spec sheet for details.

Included (available for pre-shipment)

BB2033LED	Installation housing
-----------	----------------------



Recessed wall luminaire · Shielded					
		LED	A	B	C
B22135	ADA	3.4 W	7 1/2	3 1/8	4

