



BEGA

Photometric Filename: 22202_K3.ies

TEST: BE_22202
TEST LAB: BEGA
DATE: 11/5/2012
LUMINAIRE: 22 202
LAMP: 2.1W LED, 24V DC




Characteristics

IES Classification	N.A.
Longitudinal Classification	N.A.
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	35
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	15
Total Luminaire Watts	2.4
Ballast Factor	1.00
Upward Waste Light Ratio	0.50
Max. Cd.	12.4 (5H, 90V)
Max. Cd. (<90 Vert.)	12.4 (0H, 87.5V)
Max. Cd. (At 90 Deg. Vert.)	12.4 (35.4%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	12.4 (35.4%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	0.8	N.A.	2.2
FM (30-60)	5.7	N.A.	16.2
FH (60-80)	7.0	N.A.	20.0
FVH(80-90)	4.0	N.A.	11.5
BL (0-30)	0.0	N.A.	0.0
BM (30-60)	0.0	N.A.	0.0
BH (60-80)	0.0	N.A.	0.0
BVH(80-90)	0.0	N.A.	0.0
UL (90-100)	4.0	N.A.	11.5
UH (100-180)	13.5	N.A.	38.5
Total	35.0	N.A.	100.0

BUG Rating B0-U2-G0



Mounting Height = 1 ft. Grid Spacing = 1 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2019

09/23/2019