

Application

Designed for low mounting heights for interior and exterior locations, the asymmetric distribution provides light in a forward orientation and is suitable for lighting ground surfaces, building entrances, and stairways.

Materials

- Clear safety glass
- Die-cast aluminum
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel screw clamps
- Aluminum installation housing
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 0.6 lbs.

Electrical

| | |
|------------------------|-----------|
| LED module wattage | 2.1 W |
| System wattage | 3.1 W |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 43 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

| | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:

BEGA Product:

Project:

Modified:

Available options

| | |
|-----|---------------------------------|
| CUS | Custom finish |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL finish |


Available accessories

| | |
|--------|----------------------------------|
| B19580 | Remote driver box · Static white |
| B19591 | Remote driver box · Static white |

See individual accessory spec sheet for details.

Included (available for pre-shipment)

| | |
|-----------|----------------------|
| BB2002LED | Installation housing |
|-----------|----------------------|



| Recessed wall luminaire · Directed light · 24V DC | | | | |
|---|-----|-------|-------|---|
| | | LED | A | B |
| B22230 | ADA | 2.1 W | 3 1/8 | 4 |

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2025 Updated 07/17/25

