

Application

As individual luminaires with low mounting height, they can be used for marking danger areas or in rows for illuminating corridors and passageways. With high mounting heights they can be used as wall luminaires next to doors or for lighting small wall areas.

Materials

- Clear safety glass with matte finish
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 64

Weight: 1.5 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	4.2W
System wattage	5.8W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	362lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.


Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:  
BEGA Product:  
Project:  
Modified:

Available options

CUS	Custom finish
DALI-2	Enabled for DALI control system
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish



Wall luminaire · Directed light					
		LED	A	B	C
B22261	ADA	4.2 W	6 <sup>7</sup> / <sub>8</sub>	3 <sup>3</sup> / <sub>4</sub>	2 <sup>3</sup> / <sub>8</sub>

