

Application

This wall mounted luminaire has light output in two directions. Arranged individually or in groups, it is a great design element for a host of lighting applications.

Materials

- Clear safety glass with matte finish
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.1 lbs.

Electrical

- | | |
|---------------------------|--------------------------------|
| Operating voltage | 120-277VAC |
| Minimum start temperature | -30° C |
| LED module wattage | 7.7 W |
| System wattage | 10.0 W |
| Controllability | 0-10V, TRIAC, and ELV dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 704 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.


Available colors

- | | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:
BEGA Product:
Project:
Modified:

Available options

- | | |
|-----|---------------------------------|
| AMB | Amber LED |
| CUS | Custom finish |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish |



Wall luminaire · Light emission on two sides				
	LED	A	B	C
B22363	ADA 7.7 W	8 1/2	4 3/8	4

