

Application
The exceptional material thickness and strength of crystal glass provides this luminaire with robustness and defines its character. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials
Pressed crystal glass with white ceramic coating on one side
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.2 lbs.

Electrical	
Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	2.9W
System wattage	5.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	243lm
LED service life (L70)	60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options	
CUS	Custom finish
DALI-2	Enabled for DALI control system
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish



Impact-resistant wall luminaire · Unshielded				
	LED	A	B	C
B22423	2.9W	4 ³ / ₄	4 ³ / ₄	6 ³ / ₈

