

Application

Designed for indirect or direct lighting effects for interior and exterior locations. This wall luminaire is for illuminating surfaces adjacent to the installation surface, such as ceilings, arches, and canopies. DarkSky Approved when installed facing down (2700K and 3000K only)

Materials

- Clear safety glass with white ceramic coating
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.5 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	25.3 W
System wattage	32.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1784 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3) (DarkSky Approved)
- 2700K (K27) (DarkSky Approved)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:


Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

Included (available for pre-shipment)

B19538	Small opening wiring box
--------	--------------------------



Wall washer · Asymmetric			
	LED	A	B
B22433	25.3 W	6 1/2	6 5/8

