


BEGA

Photometric Filename: 22453.IES

TEST: BE3752
TEST LAB: BEGA
DATE: 10/12/2017
LUMINAIRE: 22 453
LAMP: 3.9W LED




Characteristics

IES Classification	Type VS
Longitudinal Classification	Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	370
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	62
Total Luminaire Watts	6
Ballast Factor	1.00
Upward Waste Light Ratio	0.39
Max. Cd.	44 (45H, 57.5V)
Max. Cd. (<90 Vert.)	44 (45H, 57.5V)
Max. Cd. (At 90 Deg. Vert.)	37.3 (10.1%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	37.7 (10.2%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	13.0	N.A.	3.5
FM (30-60)	44.7	N.A.	12.1
FH (60-80)	36.9	N.A.	10.0
FVH (80-90)	17.8	N.A.	4.8
BL (0-30)	13.0	N.A.	3.5
BM (30-60)	44.7	N.A.	12.1
BH (60-80)	36.9	N.A.	10.0
BVH (80-90)	17.8	N.A.	4.8
UL (90-100)	35.0	N.A.	9.4
UH (100-180)	110.3	N.A.	29.8
Total	370.1	N.A.	100.0

BUG Rating B0-U3-G1



Mounting Height = 5 ft. Grid Spacing = 5 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2017

10/12/2017