


BEGA

Photometric Filename: 22470.ies

TEST: BE_22470
TEST LAB: BEGA
DATE: 5/4/2016
LUMINAIRE: 22 470
LAMP: 11.8W LED




Characteristics


Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1220
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	81
Total Luminaire Watts	15
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.28
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.42
Basic Luminous Shape	Circular w/ Sides
Luminous Length (0-180)	0.00 ft
Luminous Width (90-270)	0.72 ft (Diameter)
Luminous Height	0.16 ft

Zonal Lumen Summary

Zone	Lumens
0-10	34.42
10-20	99.01
20-30	151.21
30-40	184.40
40-50	194.52
50-60	181.65
60-70	150.18
70-80	108.48
80-90	67.16
90-100	34.21
100-110	12.71
110-120	2.34
120-130	0.01
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.01
170-180	0.02



Ceiling Mount - Isofootcandle grid on floor
Mounting Height = 10 ft. Grid Spacing = 10 ft.



Wall Mount - Isofootcandle grid on floor
Mounting Height = 5 ft. Grid Spacing = 10 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.