

Application

The shielded light distribution is ideal for the glare-free illumination of ground surfaces, building entrances, stairs, and footpaths.

Materials

Luminaire housing and faceplate constructed of die-cast marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
Clear safety glass with optical texture
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Stainless steel screw clamps
Painted aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 0.5lbs

Electrical

Operating voltage	24VDC (remote power supply req.)
LED module wattage	2.0W
System wattage	2.7W
Color rendering index	Ra > 80
Luminaire lumens	44 lumens (3000K)
Lifetime at Ta = 25° C	50,000 h (L70)

LED color temperature

4000K - Product number + **K4**
3500K - Product number + **K35**
3000K - Product number + **K3 (EXPRESS)**
2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors	Black (BLK)	White (WHT)	RAL:
	Bronze (BRZ)	Silver (SLV)	CUS:

Type:

BEGA Product:


Project:


Modified:

Available Accessories

19580 Remote 25W LED driver and box
19591 Remote 50W LED driver and box

See individual accessory spec sheet for details.



LED recessed wall · shielded				
	LED	A	B	C
22794 	2.0W	3 1/8	4	3/4

