


Tools Required:

- 3mm hex key
- 4mm hex key
- Philips medium screwdriver



- Dimensions**
- A: 13-3/4 "
- B: 3-3/8 "
- C: 9-1/2 "



Weight: 5.7 lbs.


Notice to Installer for 23 410:

1. See page 2 for specific product safety warnings.
2. For interior or damp rated locations only.
3. Luminaire mounts directly to surface OVER a 4" standard octagonal wiring box (by others).
4. Integral LED module and LED Driver included.
5. LEDs are high-quality electronic components! Please avoid touching the light output opening of the LED directly during installation.

23 410 - installation:

1. Unscrew glass from luminaire to remove glass.
2. Route the luminaire wiring through the back plate.
3. Make supply wiring and luminaire wiring connections inside wiring box:
MAIN VOLTAGE SUPPLY WIRE TO BLACK DRIVER WIRE(S);
NEUTRAL (COMMON SUPPLY WIRE TO WHITE DRIVER WIRE(S);
GREEN GROUND WIRE TO GREEN DRIVER WIRE(S).
4. Attach the back plate directly to finished surface over a 4" standard octagonal wiring box using hardware (by others).
5. Screw glass by twist-lock closure, assuring a snug fit against housing.

Figure 1



Relamping/Maintenance

Loosen set screw on side of luminaire housing. Remove lens from luminaire base. Clean glass and luminaire using only solvent-free cleansers. Replace lens and tighten set screw.

Accessories

Please refer to the appropriate accessory installation sheet for further instruction when applicable.

Replacement Parts

Description	Part No
Diffuser	112940.1
LED Driver (120V-277V)	75990
LED Module (3000K)	LED-0529/930
LED Module (4000K)	LED-0529/940

Lamp: 11.9W LED

Product Safety Warnings:

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED. SUITABLE FOR DAMP LOCATIONS.

MIN 90°C SUPPLY CONDUCTORS.

CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS. CONVIENT AUX EMPLACEMENTS HUMIDES.

LES FILS D'ALIMENTATION 90°C MIN.
