

Application

Ceiling luminaires with diffuse broad spread light distribution. The distinctive hand-blown, three-ply opal glass with concave interior surface provides a soft, uniform light gradient. The compact, shallow housing is ideal for areas with low ceiling heights such as lobbies and corridors.

Materials

Hand-blown opal glass  
Aluminum housing

NRTL listed to North American Standards, for interior use only

Weight: 1.6 lbs.

Electrical

|                           |                |
|---------------------------|----------------|
| Operating voltage         | 120-277VAC     |
| Minimum start temperature | -20° C         |
| LED module wattage        | 7.5W           |
| System wattage            | 9.0W           |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 80        |
| Luminaire lumens          | 527 lm         |
| LED service life (L70)    | 60000hrs       |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Polished aluminum (.3)
- Stainless steel (.2)

Type:

BEGA Product:

Project:

Modified:



Ceiling luminaire · Opal glass

|        | LED  | A                             | B                             |
|--------|------|-------------------------------|-------------------------------|
| B23966 | 7.5W | 4 <sup>7</sup> / <sub>8</sub> | 3 <sup>7</sup> / <sub>8</sub> |

