

Application

Ceiling luminaires with diffuse broad spread light distribution. The distinctive hand-blown, three-ply opal glass with concave interior surface provides a soft, uniform light gradient. The compact, shallow housing is ideal for areas with low ceiling heights such as lobbies and corridors.

Materials

Hand-blown opal glass
Aluminum housing

NRTL listed to North American Standards, for interior use only

Weight: 2.4 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	9.6W
System wattage	12.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	939lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Polished aluminum (.3)
- Stainless steel (.2)

Type:

BEGA Product:

Project:

Modified:



Ceiling luminaire · Opal glass

	LED	A	B
B23967	9.6W	5 ⁵ / ₈	4 ³ / ₈

