

Application

Ceiling and wall luminaire with hand-blown, satin matte opal glass for a soft and uniform light distribution. Some of the light exits behind the shield and also illuminates the mounting surface.

Materials

Three-ply opal glass with satin matte finish
A380 aluminum alloy
Stainless steel housing
High temperature silicone gasket
Stainless steel mounting plate

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.17 lbs.

Electrical

| | |
|-----------------------------|----------------|
| Operating voltage | 120-277V AC |
| Minimum start temperature | -30° C |
| Maximum ambient temperature | 50° C |
| LED module wattage | 14.2 W |
| System wattage | 18.0 W |
| Controllability | 0-10V dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 1557 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.


Available colors

| | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:
BEGA Product:
Project:
Modified:

Available options

| | |
|-----------|--|
| CUS | Custom finish |
| DALI | Digital addressable lighting interface |
| ELV/TRIAC | Electronic low voltage/TRIAC dimming |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL finish |



| Ceiling and wall luminaire · Opal glass | | | | | |
|---|-----|--------|--------------------------------|-------------------------------|-------------------------------|
| | | LED | A | B | C |
| B24043 | ADA | 14.2 W | 12 ⁷ / ₈ | 3 ⁵ / ₈ | 9 ⁷ / ₈ |

