

Application

Designed for accent lighting of walls and facades. Two wide beams of light produce a striking pattern on the installation surface in any orientation.

Materials

Clear safety glass with optical texture
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Silicone applied robotically to casting, plasma treated for increased adhesion
Mechanically captive stainless steel fasteners
Galvanized zinc-plated mounting bracket
Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.1 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 10.0 W
System wattage 12.0 W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 80
Luminaire lumens 437 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish



Wall luminaire · Two 90° ports					
		LED	A	B	C
B24087	ADA	10.0 W	4 ³ / ₄	7	2 ³ / ₄