

**Application**  
Recessed wall luminaire with shielded light for glare-free illumination of ground surfaces and way finding.

**Materials**  
BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 1.9 lbs.

<b>Electrical</b>	
Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	1.9W
System wattage	6.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	10 lm
LED service life (L70)	60000 hrs

- LED color temperature**
- 4000K (K4)
  - 3500K (K35)
  - 3000K (K3)
  - 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

<b>Available colors</b>	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:  
BEGA Product:  
Project:  
Modified:

<b>Available options</b>	
CUS	Custom finish
DALI-2	Enabled for DALI control system
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

**Included (available for pre-shipment)**  
BB24011      Installation housing



Recessed wall luminaire · Shielded				
		LED	A	B
B24101	ADA	1.9W	5 1/8	5 1/2