

Application

Recessed wall luminaire with unshielded light distribution for the illumination of ground surfaces, building entrances, plazas, and footpaths.

Materials

- Clear safety glass with white ceramic coating
- Corrosion-resistant 304 grade stainless steel
- Mechanically captive stainless steel fasteners
- High temperature silicone gasket
- Aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 28.9lbs.

Electrical

- | | |
|---------------------------|----------------|
| Operating voltage | 120-277VAC |
| Minimum start temperature | -30° C |
| LED module wattage | 23.6W |
| System wattage | 26.0W |
| Controllability | 0-10V dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 1305lm |
| LED service life (L70) | 60000hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:

Available options

- FSC
- Fusing

Included (available for pre-shipment)

- BB24105
- Installation housing



Recessed wall luminaire · Unshielded				
	LED	A	B	C
B24105	23.6W	49	5	5

