

Application

Recessed wall luminaire with directed light distribution for the illumination of ground surfaces, building entrances, plazas, and footpaths from a low mounting height.

Materials

- Clear safety glass with optical texture
- Corrosion-resistant 304 grade stainless steel
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Aluminum installation housing

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 67

Weight: 19.0 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage27.0 W
- System wattage31.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens2392 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:  
BEGA Product:  
Project:  
Modified:

Available options  
FSC      Fusing

Included (available for pre-shipment)  
BB24105      Installation housing



Recessed wall luminaire · Directed light				
	LED	A	B	C
B24108	27.0W	49	5	5

