

Application

A ceiling and wall luminaire offering quality illumination with maximum visual comfort. Arranged individually as bands of light, or in groups, this luminaire is an effective design element.

Materials

- White UV-stabilized acrylic diffuser
- Extruded aluminum
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 7.5 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage11.1 W
- System wattage18.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens1899 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:


BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL finish



| Ceiling and wall luminaire · Unshielded |        |                                |                               |                               |
|---|--------|--------------------------------|-------------------------------|-------------------------------|
|   | LED    | A                              | B                             | C                             |
| B24115                                  | 11.1 W | 19 <sup>5</sup> / <sub>8</sub> | 4 <sup>7</sup> / <sub>8</sub> | 4 <sup>3</sup> / <sub>4</sub> |

