

**Application**  
Recessed wall luminaire with shielded light distribution for glare-free illumination of ground surfaces, building entrances, stairs and pathways.

**Materials**  
BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 3.3 lbs.

|                           |                |
|---------------------------|----------------|
| <b>Electrical</b>         |                |
| Operating voltage         | 120-277V AC    |
| Minimum start temperature | -30° C         |
| LED module wattage        | 7.7 W          |
| System wattage            | 11.0 W         |
| Controllability           | 0-10V dimmable |
| Color rendering index     | Ra > 80        |
| Luminaire lumens          | 565 lm         |
| LED service life (L70)    | 60000 hrs      |

- LED color temperature**
- 4000K (K4)
  - 3500K (K35)
  - 3000K (K3)
  - 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


**Finish**  
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

|                         |              |
|-------------------------|--------------|
| <b>Available colors</b> |              |
| Black (BLK)             | Bronze (BRZ) |
| Silver (SLV)            | White (WHT)  |
| Natural Bronze (NTB)    | RAL:         |
| CUS:                    |              |

Type:  
BEGA Product:  
Project:  
Modified:

|                          |                                 |
|--------------------------|---------------------------------|
| <b>Available options</b> |                                 |
| CUS                      | Custom finish                   |
| MGU                      | Marine grade undercoat          |
| NTB                      | Natural bronze (premium finish) |
| RAL                      | RAL Classic, matte finish       |

**Included (available for pre-shipment)**  
BB24012      Installation housing



| Recessed wall luminaire · Shielded |           |                               |                               |                               |
|------------------------------------|-----------|-------------------------------|-------------------------------|-------------------------------|
|                                    | LED       | A                             | B                             | C                             |
| <b>B24152</b>                      | ADA 7.7 W | 7 <sup>3</sup> / <sub>8</sub> | 5 <sup>1</sup> / <sub>2</sub> | 1 <sup>1</sup> / <sub>4</sub> |

