

Application

Recessed wall luminaire with shielded light distribution for glare-free illumination of ground surfaces, building entrances, stairs and pathways.

Materials

Clear safety glass with optical texture
BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
Stainless steel screw clamps
Mechanically captive stainless steel fasteners
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.3 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	4.8 W
System wattage	7.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	488 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:


Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish

Included (available for pre-shipment)

BB24216 Installation housing



Recessed wall luminaire · Shielded				
	LED	A	B	C
B24203	ADA 4.8 W	7 1/2	7 1/2	5 1/4

