

Application

Recessed wall luminaire with directed light distribution for the illumination of ground surfaces, stairs and pathways.

Materials

- Clear safety glass with optical texture
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Stainless steel screw clamps
- Mechanically captive stainless steel fasteners
- Stainless steel helicoils
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.3 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage4.8W
- System wattage7.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens739lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)

Bronze (BRZ)


Silver (SLV)

White (WHT)

Natural Bronze (NTB)

RAL:

CUS:



Recessed wall luminaire · Directed light					
		LED	A	B	C
B24207	ADA	4.8W	7 1/2	7 1/2	5 1/4

Type:

BEGA Product:

Project:

Modified:

Available options

- CUS

MGU

NTB

RAL
- Custom finish

Marine grade undercoat

Natural bronze (premium finish)

RAL finish

Included (available for pre-shipment)

- BB24216

Installation housing

