

Application

Recessed wall luminaire with directed light distribution for the illumination of ground surfaces, stairs and pathways.

Materials

- Clear safety glass with optical texture
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Stainless steel screw clamps
- Mechanically captive stainless steel fasteners
- Stainless steel helicoils
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Composite installation housing

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 4.9 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	11.6W
System wattage	22.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1762lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:


Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish

Included (available for pre-shipment)

BB24217	Installation housing
---------	----------------------



Recessed wall luminaire · Directed light					
		LED	A	B	C
<b>B24208</b>	<b>ADA</b>	11.6W	9 <sup>7</sup> / <sub>8</sub>	9 <sup>7</sup> / <sub>8</sub>	5 <sup>1</sup> / <sub>4</sub>

