Application

Recessed wall luminaire with forward throw light distribution for the illumination of ground surfaces, stairs and pathways.

Materials

Clear safety glass with optical texture

BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection

High temperature silicone gasket

Mechanically captive stainless steel fasteners

Silicone applied robotically to casting, plasma treated for increased adhesion

Stainless steel helicoils

Stainless steel screw clamps

Composite installation housing

NRTL listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 3.1 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 4.8 W
System wattage 7.0 W

Controllability 0-10V dimmable

Color rendering index Ra > 80 Luminaire lumens 581 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:

CUS:

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish

Included (available for pre-shipment)

BB24216 Installation housing





Recessed wall luminaire · Asymmetric

		LED	А	В	С	
B24211	ADA	4.8 W	71/.	71/.	51/.	