

Application
Recessed wall luminaire with unshielded light distribution for the illumination of ground surfaces, building entrances, stairs and pathways.

Materials
BEGA Tricoat ®, a 3-layer finishing technology for increased corrosion protection

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.1 lbs.

Electrical	
Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	11.5 W
System wattage	16.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1258 lm
LED service life (L70)	60000 hrs

- LED color temperature**
- 4000K (K4)
 - 3500K (K35)
 - 3000K (K3)
 - 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options	
CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish

Included (available for pre-shipment)
BB24216 Installation housing



Recessed wall luminaire · Unshielded					
		LED	A	B	C
B24216	ADA	11.5 W	7 1/2	7 1/2	5 1/4