


Tools Required:

Phillips medium screwdriver
Standard medium screwdriver

Dimensions

A: 15-1/8"
B: 4-3/8"



Protection Class: IP65

Weight: 7.72 lbs.

Notice to Installer for 24 222:


- 1. BEGA luminaires may be damaged if connected to conduit systems containing water- Article 300-5G of National Electric Code requires that “Conduits or raceways through which moisture may contact energized live parts shall be sealed or plugged at either or both ends”.
- 2. Mounts directly to ceiling or wall OVER standard recessed 4” octagonal wiring box (by others).
- 3. In conformance with U.L. Standards 1598, a silicone-based sealant MUST be used between the mounting plate edge and supporting wall.
- 4. LEDs are high-quality electronic components! Please avoid touching the light output opening of the LED directly during installation.

24 222 - Installation:

- 1. Turn diffuser counter-clockwise remove lens from luminaire base, carefully.
- 2. Feed luminaire wires through luminaire base.
- 3. Make supply wiring and luminaire wiring connections in the octagonal wiring box:
MAIN VOLTAGE SUPPLY WIRE TO BLACK LUMINAIRE WIRE
NEUTRAL (COMMON) SUPPLY WIRE TO WHITE LUMINAIRE WIRE
GREEN GROUND WIRE TO GREEN LUMINAIRE WIRE

Dimming (if applicable):

- DIMMING CONTROL WIRE (+) TO POSITIVE DRIVER DIM CONTROL WIRE
DIMMING CONTROL WIRE (-) TO NEGATIVE DRIVER DIM CONTROL WIRE
- 4. Mount luminaire to ceiling over recessed wiring box using hardware by others (minimum size 8-32 screws, see figures).
- 5. Replace diffuser by turning clockwise.



Relamping/Maintenance

No relamping required

Accessories

Please refer to the appropriate accessory installation sheet for further instruction when applicable.

Replacement Parts

Description	Part No
Glass	112505.1
LED Driver	75983-02
LED Module (3000K)	LED-0854/930
LED Module (4000K)	LED-0854/940

Lamp: 20.2W LED

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

Product Safety Warnings:

CAUTION - RISK OF FIRE. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED. SUITABLE FOR WET LOCATIONS.

MIN 90°C SUPPLY CONDUCTORS.

ATTENTION - RISQUE D'INCENDIE, CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS. CONVIENT AUX EMPLACEMENTS MOUILLÉS.

LES FILS D'ALIMENTATION 90°C MIN.
