

**Application**  
Ceiling and wall luminaires with impact-resistant polyethylene diffuser. The impact-resistant diffuser adds strength and security in locations where glass cannot be used. This luminaire can be utilized individually or in groups for glare-free illumination of interior and exterior spaces.

**Materials**  
White high-density polyethylene diffuser  
Die-cast aluminum  
High temperature silicone gasket  
**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65  
**Weight:** 2.7 lbs.

**Electrical**  
Operating voltage 120-277VAC  
Minimum start temperature -40° C  
LED module wattage 8.4W  
System wattage 10.0W  
Controllability 0-10V dimmable  
Color rendering index Ra > 90  
Luminaire lumens 879lm  
LED service life (L70) 60000hrs


**LED color temperature**  
4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)  
**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**  
Black (BLK) Bronze (BRZ)  
Silver (SLV) White (WHT)  
Natural Bronze (NTB) RAL:  
CUS:

Type:  
BEGA Product:  
Project:  
Modified:

**Available options**  
CUS Custom finish  
MGU Marine grade undercoat  
NTB Natural bronze (premium finish)  
RAL RAL finish



Ceiling and wall luminaire · Polyethylene			
	LED	A	B
B24225	8.4 W	11	4 1/8

