

Application
Ceiling and wall luminaires with impact-resistant polyethylene diffuser. The impact-resistant diffuser adds strength and security in locations where glass cannot be used. This luminaire can be utilized individually or in groups for glare-free illumination of interior and exterior spaces.

Materials
White high-density polyethylene diffuser
Die-cast aluminum
High temperature silicone gasket
NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65
Weight: 4.0 lbs.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 15.6W
System wattage 19.0W
Controllability 0-10V dimmable
Color rendering index Ra > 90
Luminaire lumens 1785lm
LED service life (L70) 60000hrs


LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)
BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish



Ceiling and wall luminaire · Polyethylene			
	LED	A	B
B24226	15.6W	13	4 ³ / ₈

