

Application

Recessed downlights with an asymmetric distribution designed for the illumination of walls in corridors and other interior and exterior locations.

Materials

- Clear safety glass with matte finish
- 316 grade stainless steel
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box
- Pure anodized aluminum reflector surface
- Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.8 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
LED module wattage	8.5W
System wattage	10.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	622lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Stainless steel finish. Custom colors not available.

Type:
BEGA Product:
Project:
Modified:

Available options	
DALI-2	Enabled for DALI control system
ELV/TRIAC	Electronic low voltage/TRIAC dimming
FRO	Frosted lens
FSC	Fusing



Downlight · Asymmetric wall washer				
	LED	A	B	C
B24299	8.5W	4 3/4	0 1/4	2 3/4

