



BEGA

Photometric Filename: 24303.ies

TEST: BE_24303
TEST LAB: BEGA
DATE: 4/12/2017
LUMINAIRE: 24 303
LAMP: 16W LED




Characteristics


NEMA Type	5 H x 5 V
Maximum Candela	2452.3
Maximum Candela Angle	0 H 0 V
Horizontal Beam Angle (50%)	55.0
Vertical Beam Angle (50%)	54.9
Horizontal Field Angle (10%)	82.7
Vertical Field Angle (10%)	81.2
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	1367
Beam Efficiency	N.A.
Field Lumens	2057
Field Efficiency	N.A.
Spill Lumens	104
Luminaire Lumens	2161
Total Efficiency	N.A.
Total Luminaire Watts	19

Zonal Lumen Summary

Zone	Lumens
0-10	229.60
10-20	598.07
20-30	667.51
30-40	463.19
40-50	152.78
50-60	30.02
60-70	10.36
70-80	3.70
80-90	0.33
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00



Mouting Height = 20 ft. Grid Spacing = 10 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

1/4/2018