


BEGA

Photometric Filename: 24310.ies

TEST: BE_24310
TEST LAB: BEGA
DATE: 5/10/2017
LUMINAIRE: 24 310
LAMP: 32W LED




Characteristics


NEMA Type	4 H x 4 V
Maximum Candela	7850.1
Maximum Candela Angle	0 H 0 V
Horizontal Beam Angle (50%)	34.8
Vertical Beam Angle (50%)	34.1
Horizontal Field Angle (10%)	64.0
Vertical Field Angle (10%)	62.2
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	1607
Beam Efficiency	N.A.
Field Lumens	2847
Field Efficiency	N.A.
Spill Lumens	368
Luminaire Lumens	3214
Total Efficiency	N.A.
Total Luminaire Watts	36

Zonal Lumen Summary

Zone	Lumens
0-10	661.87
10-20	1265.09
20-30	857.14
30-40	298.79
40-50	81.55
50-60	27.83
60-70	12.41
70-80	4.53
80-90	0.51
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00



Mouting Height = 20 ft. Grid Spacing = 10 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

1/24/2018