Application

Linear LED ceiling mounted luminaire with asymmetrical light distribution. The patent pending 'vortex reflector' rotates a parabolic reflector around the vertical axis to form a complex vortex shape. This vortex balances maximum efficiency with optimal glare control while eliminating shadows and artifacts in a uniquely sharp square distribution.

Materials

Luminaire housing constructed of die-cast marine grade, copper free (\leq 0.3% copper content) A360.0 aluminum alloy Clear safety glass

Reflector surface made of pure anodized aluminum

Silicone applied robotically to casting, plasma treated for increased adhesion

Mechanically captive stainless steel fasteners

 \mbox{NRTL} listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 20.3 lbs

Electrical

Operating voltage 120-277V AC
Minimum start temperature -20° C
LED module wattage 48.0 W
System wattage 55.0 W

Controllability 0-10V dimming down to 0.1%

Color rendering index Ra>80

 $\begin{array}{lll} \mbox{Luminaire lumens} & \mbox{6,100 lumens (3000K)} \\ \mbox{Lifetime at Ta} = 15^{\circ}\mbox{C} & >500,000\ \mbox{h (L70)} \\ \mbox{Lifetime at Ta} = 50^{\circ}\mbox{C} & 78,000\ \mbox{h (L70)} \\ \end{array}$

LED color temperature

4000K - Product number + **K4** 3500K - Product number + **K35** 3000K - Product number + **K3** 2700K - Product number + **K27**

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured polyester powder coat with minimum 3 mil thickness.

Available colors Black (BLK) White (WHT) RAL: Bronze (BRZ) Silver (SLV) CUS:

Type:

BEGA Product:

Project:

Modified:



LED ceiling mounted downlights · vortex reflector · asymmetrical light							
	LED	β	А	В	С	Required wiring box	
24314	48.0 W	55°	59 1/4	2 3/8	3 3/4	19537	

 β = Beam angle