

Application
Linear ceiling and wall luminaire with unshielded light distribution. Arranged individually, in continuous bands of light or grouped together, these luminaires can accentuate building architecture while providing glare free illumination.

Materials
Clear safety glass with white ceramic coating
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Silicone applied robotically to casting, plasma treated for increased adhesion
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 11.9lbs.

Electrical
Operating voltage 120-277V AC
Minimum start temperature -20° C
LED module wattage 32.0 W
System wattage 36.0 W
Controllability 0-10V dimming down to 0.1%
Color rendering index Ra > 80
Luminaire lumens 2039 lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish

Included (available for pre-shipment)
B19537 Narrow opening wiring box



Linear ceiling and wall luminaire · Unshielded				
	LED	A	B	C
B24319	32.0W	40	2 ³ / ₈	3 ³ / ₄

