

**Application**  
Linear ceiling and wall luminaire with unshielded light distribution. Arranged individually, in continuous bands of light or grouped together, these luminaires can accentuate building architecture while providing glare free illumination.

**Materials**  
Clear safety glass with white ceramic coating  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Silicone applied robotically to casting, plasma treated for increased adhesion  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 20.1 lbs.

**Electrical**  
Operating voltage 120-277V AC  
Minimum start temperature -20° C  
LED module wattage 48.0 W  
System wattage 55.0 W  
Controllability 0-10V dimming down to 0.1%  
Color rendering index Ra > 80  
Luminaire lumens 3361 lm  
LED service life (L70) 60000 hrs

**LED color temperature**  
4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**  
Black (BLK) Bronze (BRZ)  
Silver (SLV) White (WHT)  
Natural Bronze (NTB) RAL:  
CUS:

Type:  
BEGA Product:  
Project:  
Modified:

**Available options**  
CUS Custom finish  
FSC Fusing  
MGU Marine grade undercoat  
NTB Natural bronze (premium finish)  
RAL RAL finish

**Included (available for pre-shipment)**  
B19537 Narrow opening wiring box



Linear ceiling and wall luminaire · Unshielded				
	LED	A	B	C
B24320	48.0 W	59 1/4	2 3/8	3 3/4