

Application

Recessed downlights with an asymmetric distribution designed for the illumination of walls in corridors and other interior and exterior locations.

Materials

- Clear safety glass with matte finish
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- 316 grade stainless steel
- Stainless steel screw clamps
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Galvanized steel rough in ceiling pan with through wiring junction box
- Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 7.5 lbs.

Electrical

|                           |                          |
|---------------------------|--------------------------|
| Operating voltage         | 120-277VAC               |
| Minimum start temperature | -20° C                   |
| LED module wattage        | 25.0W                    |
| System wattage            | 28.0W                    |
| Controllability           | 0-10V dimming down to 1% |
| Color rendering index     | Ra > 90                  |
| Luminaire lumens          | 2471 lm                  |
| LED service life (L70)    | 60000hrs                 |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Stainless steel finish. Custom colors not available.

Type:

BEGA Product:

Project:


Modified:

Available options

|           |                                      |
|-----------|--------------------------------------|
| DALI-2    | Enabled for DALI control system      |
| ELV/TRIAC | Electronic low voltage/TRIAC dimming |
| FRO       | Frosted lens                         |
| FSC       | Fusing                               |

Included (available for pre-shipment)

|         |             |
|---------|-------------|
| CP24265 | Ceiling pan |
|---------|-------------|



| Downlight · Asymmetric wall washer |       |       |       |       |
|------------------------------------|-------|-------|-------|-------|
|                                    | LED   | A     | B     | C     |
| B24326                             | 25.0W | 9 1/2 | 0 1/4 | 4 1/2 |

