

Application

Wall mount luminaire with asymmetric light distribution designed for the illumination of parking areas and roadways.

Materials

- Clear safety glass with optical texture
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High-strength A572 stainless steel alloy
- High temperature silicone gasket
- Integral surge protector
- Stainless steel mounting plate
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 66

Weight: 9.5 lbs.

EPA (Effective projection area): 0.32 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- Maximum ambient temperature90° C
- LED module wattage12.6W
- System wattage17.0W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens2063 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:

BEGA Product:

Project:

Modified:



Available options

- | | |
|--------|--|
| AMB | Amber LED |
| CUS | Custom finish |
| DALI | Digital addressable lighting interface |
| FSC | Fusing |
| IMS-L2 | Integral motion sensor (48' ⌘ coverage at 8' AFG) |
| IMS-L3 | Integral motion sensor (40' ⌘ coverage at 20' AFG) |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish |

Available accessories

- BFSIR-100 Handheld configuration tool

See individual accessory spec sheet for details.



Area/roadway wall luminaire · Asymmetric

	LED	A	B	C	D
B24350	12.6W	10	2 ³ / ₈	16 ¹ / ₈	5 ¹ / ₄



BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com