

Application

Wall mounted luminaire with asymmetric light distribution, ideal for illuminating horizontal surfaces from vertical mounting surfaces.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Silicone applied robotically to casting, plasma treated for increased adhesion
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 15.9lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-20° C
- LED module wattage98.3 W
- System wattage105.0 W
- Controllability0-10V dimming down to 0.1%
- Color rendering indexRa > 80
- Luminaire lumens10523 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|----------------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| Natural Bronze (NTB) | RAL: |
| CUS: | |

Type:


BEGA Product:

Project:

Modified:

Available options

- | | |
|-----|---------------------------------|
| CUS | Custom finish |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| NTB | Natural bronze (premium finish) |
| RAL | RAL Classic, matte finish |



Wall luminaire · Asymmetric

	LED	A	B	C	D
B24352	98.3 W	12 ³ / ₈	4 ⁵ / ₈	22 ¹ / ₂	5 ¹ / ₄

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2025 Updated 09/12/25