

**Application**  
A robust and timeless ceiling and wall luminaire for a host of lighting applications. Fasteners are not visible on the front of the housing adding to the elegance of this design.

**Materials**  
Pressed crystal glass with white ceramic coating on one side  
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Mechanically captive stainless steel fasteners

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 2.4 lbs.

<b>Electrical</b>	
Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	6.0W
System wattage	7.5W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	557 lm
LED service life (L70)	60000hrs

**LED color temperature**  
4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

<b>Available colors</b>	
Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:  
BEGA Product:  
Project:  
Modified:

<b>Available options</b>	
CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish



Ceiling and wall luminaire · Unshielded with safety guard · crystal glass

		LED	A	B	C
<b>B24353</b>	<b>ADA</b>	6.0W	8 <sup>5</sup> / <sub>8</sub>	4 <sup>3</sup> / <sub>4</sub>	3

