

Application
A robust and timeless ceiling and wall luminaire for a host of lighting applications. Fasteners are not visible on the front of the housing adding to the elegance of this design.

Materials
White UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.1 lbs.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 6.0W
System wattage 7.5W
Controllability 0-10V, TRIAC, and ELV dimmable
Color rendering index Ra > 80
Luminaire lumens 541 lm
LED service life (L70) 60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish



Ceiling and wall luminaire · Unshielded with safety guard · synthetic					
		LED	A	B	C
B24357	ADA	6.0W	8 ⁵ / ₈	4 ³ / ₄	3