

Application

Recessed downlight with a symmetric wide beam distribution. These luminaires are designed for down lighting atriums, canopies, passages, and other interior and exterior locations.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box
- Pure anodized aluminum reflector surface
- Silicone optic with excellent high temperature and UV stability
- BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 1.8 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	12.3W
System wattage	14.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	1238lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:


BEGA Product:


Project:

Modified:

Available options

CUS	Custom finish
DALI-2	Digital addressable lighting interface
ELV/TRIAC	Electronic low voltage/TRIAC dimming
FRO	Frosted lens
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish



Downlight · Wide beam					
	LED		A	B	C
<b>B24384</b>	12.3W	32°	4 <sup>3</sup> / <sub>8</sub>	0 <sup>1</sup> / <sub>4</sub>	2 <sup>3</sup> / <sub>4</sub>