

Application

Luminaire designed with an asymmetrical light distribution for illuminating surfaces adjacent to the installation. Suitable for interior and exterior applications, it directs light precisely onto ceilings, vaults, canopies, or ground surfaces to create indirect lighting effects that accentuate architectural geometry.

Materials

- Clear safety glass
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Stainless steel hardware
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 8.4 lbs.

Electrical

- Operating voltage120V or 277V AC
- Minimum start temperature-10° C
- LED module wattage32.6W
- System wattage46.0W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 90
- Luminaire lumens5136lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Natural Bronze (NTB)
- White (WHT)
- CUS:
- Bronze (BRZ)
- Silver (SLV)
- RAL:

Type:


BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- DALI-2Enabled for DALI control system
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish



Wall washer · Asymmetric				
	LED	A	B	C
B24435	32.6W	10 ¹ / ₄	8 ¹ / ₂	9 ³ / ₈

