

Application

Luminaire designed with a symmetrical light distribution for illuminating the wall surface directly. Suitable for interior and exterior applications, it uses the installation surface as a reflection plane to wash the mounted wall with even, uniform light that emphasizes texture and vertical form.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Stainless steel hardware
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.4 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage17.8 W
- System wattage20.0 W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 90
- Luminaire lumens1502 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.


Available colors

- Black (BLK)
- Natural Bronze (NTB)
- White (WHT)
- CUS:
- Bronze (BRZ)
- Silver (SLV)
- RAL:

Type:
BEGA Product:
Project:
Modified:

Available options

- CUSCustom finish
- DALI-2Enabled for DALI control system
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish



Wall washer · Symmetric				
	LED	A	B	C
B24436	17.8 W	6 1/2	6 5/8	7

