


BEGA

Photometric Filename: 24506_BEGA_IES.ies

TEST: BE_24506
TEST LAB: BEGA
DATE: 11/14/2016
LUMINAIRE: 24 506
LAMP: 18.6W LED




Characteristics

IES Classification	N.A.
Longitudinal Classification	N.A.
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1814
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	82
Total Luminaire Watts	22
Ballast Factor	1.00
Upward Waste Light Ratio	0.50
Max. Cd.	277.7 (45H, 90V)
Max. Cd. (<90 Vert.)	277.4 (40H, 87.5V)
Max. Cd. (At 90 Deg. Vert.)	277.7 (15.3%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	277.4 (15.3%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	25.4	N.A.	1.4
FM (30-60)	187.4	N.A.	10.3
FH (60-80)	229.8	N.A.	12.7
FVH (80-90)	131.1	N.A.	7.2
BL (0-30)	14.9	N.A.	0.8
BM (30-60)	109.0	N.A.	6.0
BH (60-80)	133.4	N.A.	7.4
BVH (80-90)	75.6	N.A.	4.2
UL (90-100)	206.8	N.A.	11.4
UH (100-180)	701.0	N.A.	38.6
Total	1814.4	N.A.	100.0

BUG Rating B1-U4-G2



Wall Mount Fixture - Isofootcandle grid on floor
Mounting Height = 5 ft. Grid Spacing = 10 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2021

2/4/2021