Pendant · Unshielded BEGA

Application

Pendant luminaire with symmetric wide beam light distribution and clear synthetic diffuser. This luminaire creates vertical illumination in addition to the downward light ideal for high activity spaces.

Materials

Clear UV-stabilized acrylic diffuser

Marine grade, copper free (\leq 0.3% copper content) A360.0 aluminum alloy

High temperature silicone gasket

Mechanically captive stainless steel fasteners

Stainless steel suspension cable

Galvanized zinc-plated mounting bracket

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 15.5 lbs.

Electrical

Operating voltage 120-277V AC Minimum start temperature LED module wattage 35.7 W System wattage 40.0 W

Controllability 0-10V dimmable

Color rendering index Ra > 80 Luminaire lumens 4519 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:



Pendant · Unshielded				
	LED	Α	В	С
B24508	35.7 W	71/2	383/4	1251/4

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

MGU Marine grade undercoat NTB Natural bronze (premium finish)

RAL RAL finish

Available accessories

B70477 Cable hanger

See individual accessory spec sheet for details.

Included (available for pre-shipment)

B19538 Small opening wiring box

