

**Application**

Wall mounted luminaire with adjustable gantry arm system for the illumination of large areas. The infinite adjustability of the outrigger arm system and the luminaire head enable many different lighting positions.

**NRTL** listed to North American Standards, suitable for wet locations

**Weight:** 44.1 lbs.

**Electrical**

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	55.3 W
System wattage	61.0 W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 80
Luminaire lumens	6672 lm
LED service life (L70)	60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	



**Wall mounted luminaire · Adjustable gantry arm**

	LED	A	B	C	D
<b>B24509</b>	55.3 W	16 <sup>3</sup> / <sub>4</sub>	4 <sup>1</sup> / <sub>8</sub>	90 <sup>1</sup> / <sub>2</sub>	8 <sup>1</sup> / <sub>4</sub>

Type:

BEGA Product:

Project:

Modified:

**Available options**

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish

