Application

Recessed downlights with an asymmetric distribution designed for the illumination of walls in corridors and other interior and exterior locations.

Materials

Clear safety glass with matte finish

Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Stainless steel screw clamps

Silicone applied robotically to casting, plasma treated for increased adhesion

Galvanized steel rough in ceiling pan with through wiring junction box Silicone optic with excellent high temperature and UV stability Pure anodized aluminum reflector surface

 \mbox{NRTL} listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 3.1 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -20° C
LED module wattage 16.8 W
System wattage 20.0 W

Controllability 0-10V dimming down to 1%

Color rendering index Ra > 90 Luminaire lumens 1620 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

DALI-2 Digital addressable lighting interface ELV/TRIAC Electronic low voltage/TRIAC dimming

FRO Frosted lens FSC Fusing

MGU Marine grade undercoat NTB Natural bronze (premium finish)

RAL RAL finish

Included (available for pre-shipment)

CP24263 Ceiling pan





Downlight · Asymmetric wall washer

	LED	Α	В	С	D	
B24566	16.8W	67/8	01/4	41/2	18	